

Pipeline and Hazardous Materials Safety Administration East Building, PHH – 30
1200 New Jersey Avenue, Southeast
Washington, D.C. 20590

DOT-SP 14631 (THIRD REVISION)

EXPIRATION DATE: January 31, 2018

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: iSi Automotive GmbH

Wien, Austria

(U.S. Agent: iSi North America Inc., Fairfield, NJ)

2. PURPOSE AND LIMITATIONS:

- a. This special permit authorizes the manufacture, marking, sale and use of non-DOT specification cylinders (pressure vessels) for use as components of automobile vehicle safety systems. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein. The most recent revision supersedes all previous revisions.
- b. FIVE YEAR TRANSPORTATION AUTHORIZATION: This special permit authorizes transportation of the pressure vessels identified herein for up to five years from the date of manufacture. This limitation does not apply to nonspecification pressure vessels when installed in air bag modules. This special permit provides no certification of safety for end use environments and life cycles.
- c. SPECIAL PERMIT SCOPE LIMITATIONS: This special permit only applies to a package when it is an article of commerce in transportation. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce. The safety analyses did not consider the hazards and risks associated with consumer use, incorporation as a component of a vehicle or other device, or other uses not associated with transportation in commerce. This special permit provides no certification of safety for end use environments and life cycles.

- 3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
- 4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.301(a)(1) and 173.302a in that the use of a non-DOT specification cylinder is not authorized, except as specified herein.
- 5. <u>BASIS</u>: This special permit is based on the application of iSi Automotive GmbH dated January 7, 2014, submitted in accordance with § 107.109.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Material Description			
Proper Shipping Name	Hazard Class/ Division	Identi- fication Number	Packing Group
Non-flammable, non-toxic gases or mixtures thereof/proper shipping name as specified in § 172.101	2.2	As appropriate	N/A
Air bag inflators, or Air bag modules, or Seat-belt pretensioners	1.4G	UN0503	II
Air bag inflators, or Air bag modules, or Seat-belt pretensioners	9	UN3268	III

Note: A vehicle safety system or component which contains a quantity of pyrotechnic materials must be classed and approved as provided for in § 173.56 of the HMR. If the pyrotechnic material augments the volume of the gas in the pressure vessel, or in any way enhances the performance of the compressed gas, the device must be tested in the same configuration as when shipped.

7. SAFETY CONTROL MEASURES:

a. <u>PACKAGING</u> - Prescribed packaging is a non-DOT specification pressure vessel meeting the drawings on file with the Office of Hazardous Materials Special Permits and Approvals (OHMSPA) and the following requirements:

March 26, 2014

- (1) The maximum service pressure at 70°F may not exceed 8,992 psig. The minimum test pressure is the pressure of the contents at 200°F. The rated service pressure may not exceed 80% of the test pressure and the water volume of each pressure vessel may not exceed one liter.
- (2) Material of construction must conform to all requirements of § 178.65(b), except that the ladle check analysis maximum carbon content must not exceed 0.20 percent.
- (3) Manufacturing requirements must conform to all requirements of § 178.65(c), except as follows:
 - (i) Welding of attachments to the cylinder after the § 178.65(f)(1) proof test is permitted in accordance with iSi Automotive weld procedures on file with OHMSPA. Following the welding, each cylinder must have a leak test performed in accordance with the iSi Automotive Quality Control Plan on file with OHMSPA.
- (4) The minimum wall thickness must be such that the wall stress meets the requirements of \$ 178.65(d).
- (5) Openings and attachments must conform to all requirements of \$ 178.65(e).
- (6) Each pressure vessel must be equipped with a pressure relief device designed to meet all the requirements for a rupture disk prescribed in the Compressed Gas Association (CGA) Pamphlet S-1.1. The pressure relief device must be capable of preventing rupture of the pressure vessel when subjected to a fire test conducted in accordance with CGA Pamphlet C-14.

b. TESTING -

- (1) Each pressure vessel must be tested as required in § 178.65(f) except that:
 - (i) The maximum duration of the shift specified in \$ 178.65(f)(3) may be extended beyond 10 hours at the discretion of the independent inspector.
- (2) The flattening test specified in § 178.65(g) is not required.

March 26, 2014

- (3) A representative motor vehicle or aircraft safety system, packaged as it would be for shipment, must be activated and no materials other than no-toxic, non-flammable vapors or gases may be expelled from the package.
- c. MARKING Each pressure vessel must be durably marked as follows:

DOT-SP 14631/8992¹
Lot No. xxxxx²
Manufacturer's Name

The Pressure Vessel May Not Be Refilled

 1 Where 8992 represents the design service pressure.

² Where xxxxx is the lot number as appropriate.

NOTE: Each line of these markings may be placed without regard to location or order on the pressure vessel.

8. SPECIAL PROVISIONS:

- a. In accordance with the provisions of Paragraph (b) of \$ 173.22a, persons may use the packaging authorized by this special permit for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this special permit.
- b. A person who is not a holder of this special permit, but receives a package covered by this special permit, may reoffer it for transportation provided no modification or change is made to the package and it is offered for transportation in conformance with this special permit and the HMR.
- c. This special permit is limited to pressure vessels used as components of a vehicle safety system. The pressure vessels are excepted from the requirements of the HMR, Part 178 when the design has been certified by an Independent Inspection Agency, approved under Part 107, Subpart I, as having met all the requirements of this special permit.
- d. The Independent Inspection Agency's design certification must include test results and documents related to explosive classification and approval. A copy of the certification must be maintained at each facility where the vehicle safety system is manufactured and by the Independent Inspection Agency for a period of 15 years from the date of completion of the design certification.

- e. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.
- f. A current copy of this special permit must be maintained at each facility where the package is manufactured under this special permit. It must be made available to a DOT representative upon request.
- g. No modifications may be made to the pressure vessel, pyrotechnic components or production vehicle safety system which would affect the performance of the vehicle safety system or its compliance with the requirements of this special permit until such modifications have been reviewed, tested and certified by an Independent Inspector as meeting the requirements of this special permit.
- h. Except when transported on passenger-carrying aircraft, devices utilizing the non-DOT specification pressure vessel authorized herein are exempt from the requirements of 49 CFR Parts 100-185 when installed in a motor vehicle or in completed vehicle components such as steering columns or door panels.
- i. Pressure, vessels, components and vehicle safety systems must be transported in strong outside packaging in accordance with \$ 173.301(a)(9).
- 9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel, passenger-carrying aircraft (may not exceed the quantity limitation specified in § 172.101, column 9A), and cargo aircraft only. (See restriction in paragraph 8(i)).
- 10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel, aircraft or motor vehicle used to transport packages covered by this special permit. The shipper must furnish a copy of this special permit to the air carrier before or at the time the shipment is tendered.

- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 <u>et</u> seq:
 - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 $\underline{\text{et seq.,}}$ when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)—"The Hazardous Materials Safety and Security Reauthorization Act of 2005" (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous

March 26, 2014

materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety -- OHMSPA, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:

for Dr. Magdy El-Sibaie

Want By

Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Material Safety Administration, U.S. Department of Transportation, East Building PHH-30, 1200 New Jersey Avenue, Southeast, Washington, D.C. 20590.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm
Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: ew/kah